

Key Features:

- ◆ High power density design
- ◆ N+X parallel redundancy, support maximum 4 units in parallel
- ◆ Online double conversion with DSP control
- ◆ Input current harmonic:<3%
- ◆ Wide input voltage range:208~478Vac
- ◆ Wide input frequency range 40~70Hz
- ◆ Optimization battery group, the quantity of battery
10~30kVA:16/18/20pcs (30~50pcs is optional)
40kVA:30~50pcs
- ◆ Maximum charging current up to 20A (Settable)
- ◆ Dual input source (optional for standard unit)
- ◆ Colorful 2.4-inch TFT LCD display and 7-inch LCD display LCD are optional
- ◆ Versatile LCD human-computer interface
- ◆ Generator compatible
- ◆ 50/60Hz frequency converter mode
- ◆ The output can meet 100% unbalanced load
- ◆ Multiple protection function: short-circuit, overload, overheat,
battery overcharge and over discharge, output low voltage and fan fault alarm
16/18/20pcs (Settable)
- ◆ Multiple communication interface's, RS232, RS485, Parallel port, Dry contact, Intelligent slot, SNMP card
(Optional), Relay card (Optional), Battery temperature sensor (Optional)



GXK-3-3-40-IE		
Capacity		40kVA / 36kW
		40kVA / 40kW
INPUT		
Nominal voltage		380/400/415Vac (3Ph+N+PE)
Operating voltage range		305~478Vac(Full load); 208~478Vac(50% load)
Operating frequency range		40~70Hz (50/60Hz Auto-Sensing)
Power factor		≥0.99
Bypass voltage range		Max.voltage:220V:+25% (Optional+10%,+15%,+20%)
		230V:+20% (Optional+10%,+15%)
		240V:+15% (Optional+10%)
		Mi. Voltage: -45% (Optional-20%,-30%)
Frequency protection range		50/60Hz±10%
ECO range		Same as bypass
Harmonic distortion (THDi)		≤3% Linear load
OUTPUT		
Output voltage		380/400/415Vac (3Ph+N+PE)
Voltage regulation		±1%
Power factor		0.9
Output frequency	Line Mode	±1%/±2%/±4%/±5%/±10% of the rated frequency (Optional)
	Bat. Mode	50/60(±0.1%)Hz
Crest factor		3:01

Harmonic distortion (THDv)		≤2% Linear load
		≤5% Non linear load
Transfer time	AC mode to Bat.Mode	0ms
	Inverter to Bypass	0ms
Output waveform		Pure Sinewave
Overload	Line Mode	≤110%,last 60min; ≤125%,last 10min; ≤150%,last 1min; > 150% turn to bypass Immediately
	Bypass Mode	≤110%,last 10min; ≤125%,last 1min; ≤150%,last 5s; > 150% turn to bypass Immediately
Efficiency		up to 94.5%
BATTERY		
Battery voltage	Standard unit	±180Vdc(2×30pcs 9Ah)(2×30pcs 7Ah optional)
	Long run unit	40kVA: ±180/192/204/ 216/228/240/252/264/ 276/288/300Vdc (30/32/ 34/36/38/40/42/44/46/48 /50pcs)
Charge Current (charge current can be set according to battery capacity installed)	Standard unit	2.7A
	Long run unit	20A (Max.)
ENVIRONMENTAL		
Operating temperature		0 ~ 40℃
Storage temperature		(-25 ~ 55℃ (No battery)
Humidity range		0 ~ 95% (Non condensing)
Altitude		<1500m,derating required when>1500m
Noise level		<64dB
PHYSICAL		
Dimension W x D×H (mm)	Standard unit	250 x 900 x 868
	Long run unit	250 x 580 x 655
Net weight (kg)		239kg (2×30pcs 9Ah)
STANDARDS		
Safety		EC/EN62040-1,IEC/EN62477-1
EMC		IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4,IEC61000-4-5,IEC61000-4-6,IEC61000-4-8