



SRV10KI

RoHS

High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions

Includes: CD with software, USB cable, User Manual

Technical Specifications

Output

Max Configurable Power (Watts)	10.0kWatts / 10.0kVA
Other Output Voltages	220, 240
Load Crest Factor	3 : 1
Topology	Double Conversion Online
Waveform type	Sine wave

Input

Input frequency	40 - 70 Hz
Other Input Voltages	220, 240

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Battery Volt-Amp-Hour Capacity	1599
Runtime	View Runtime Graph View Runtime Chart

Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating	600Joules
---------------------	-----------

Physical

Maximum Height	605MM 605CM
----------------	-------------

Maximum Height	663MM, 66.3CM
Maximum Width	190MM, 19.0CM
Maximum Depth	447MM, 44.7CM
Net Weight	65.0KG
Shipping weight	77.0KG
Shipping Height	910MM, 91.0CM
Shipping Width	320MM, 32.0CM
Shipping Depth	580MM, 58.0CM

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-3000meters
Storage Relative Humidity	0 - 95 (non-condensing) %
Storage Elevation	0-14763.6meters

Conformance

Approvals	CE, IEC 62040-1-1, IEC 62040-1-2
Standard warranty	2 years repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs